

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/014681 A1

- (51) International Patent Classification⁷: B60J 5/04 (74) Agent: ÅSLUND, Roland; SSAB Hardtech AB, S-971 88 Luleå (SE).
- (21) International Application Number: PCT/SE2003/001257
- (22) International Filing Date: 7 August 2003 (07.08.2003)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data: 0202380-2 8 August 2002 (08.08.2002) SE
- (71) Applicant (for all designated States except US): SSAB HARDTECH AB [SE/SE]; S-971 88 Luleå (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BODIN, Hans [SE/SE]; Tunnländsvägen 8, S-954 42 Södra Sunderbyn (SE). JONSSON, Martin [SE/SE]; Östra Järnvägsplanaden 6, S-972 42 Luleå (SE). KRISPINSSON, Jan [SE/SE]; Stationsgatan 24A, S-972 34 Luleå (SE). WIKSTRÖM, Lars [SE/SE]; Östra Malmgatan 23, S-972 42 Luleå (SE).
- (81) Designated States (national): AR, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: A VEHICLE DOOR AND A METHOD OF MANUFACTURING SUCH A DOOR



(57) Abstract: A supporting frame 10 of a door with an integrated side impact guard beam 22 is made of high strength steel. The outer panel 28 of the door will be close to the side impact guard beam. All the interior units of the door, such as lock and window structure 34-37 with window frame 37, are mounted on a beam structure 30. The beam structure is then mounted on the frame 10 so that the window structure will be between the frame 10 and the beam structure 30.

WO 2004/014681 A1